

建材应用指南

			推荐产品	施工性能	粘结强度	抗流挂		添加量
腻子	干粉腻子	碱性腻子	BK-01	◎	●	○		0.05-1%
			PT-02S	●	◎	◎		0.05-1%
			PT-05S	◎	○	●		0.03-0.05%
		中性腻子	BK-01	◎	●	○		0.05-1%
			PT-02S	●	◎	◎		0.05-1%
			PT-05S	◎	○	●		0.03-0.05%
		灰钙腻子	BK-01	◎	●	○		0.05-1%
			PT-02S	●	◎	◎		0.05-1%
			PT-05S	●	◎	●		0.03-0.05%
	腻子膏		BK-01	◎	●	○		0.05-1%
			PT-02S	●	◎	◎		0.05-1%
			PT-05S	◎	◎	●		0.03-0.05%
双组分腻子		PT-02S	●	◎	○		0.05-1%	
		PT-05S	◎	◎	●		0.03-0.05%	
			推荐产品	施工性能	粘结强度	抗流挂	可工作时间	添加量
瓷砖胶	C0	C0	BK-01	◎	●	○	○	0.05-1%
			BK-01	◎	●	○	○	0.05-1%
		C1/C1T	CT-02	●	◎	◎	●	0.05-1%
			CT-05	◎	◎	●	●	0.05-1%
		C2/C2T	CT-05	◎	◎	◎	●	0.03-0.05%
			CT-06	◎	◎	◎	●	0.03-0.05%
	填缝剂		CT-05	◎	◎	◎	●	0.03-0.05%
			CT-06	◎	◎	◎	●	0.03-0.05%
	美缝剂	无溶剂环氧	C72	●	○	●	○	0.03-0.05%
水性环氧		LB	●	●	●	○	0.03-0.05%	
			推荐产品	分散性	抗泌水	流平		添加量
自流平	水泥基自流平	PT-02S	●		●			0.05-1%
		PT-05S	●	●	◎			0.03-0.05%
	石膏基自流平	PT-02S	●			◎		0.05-1%
		PT-05S	●	●		◎		0.03-0.05%
			推荐产品	施工性能	粘结强度	抗流挂	表面平整性	添加量
抹灰石膏			BK-01	◎	●	○	○	0.05-1%
			PT-02S	●	◎	◎	●	0.05-1%
			PT-05S	●	◎	●	●	0.03-0.05%
			推荐产品	施工性能	粘结强度	抗流挂	表面平整性	添加量
普通机喷砂浆			BK-01	●	●	○	◎	0.05-1%
			PT-05S	●	◎	●	●	0.03-0.05%
○ 适用 ◎ 推荐 ● 最佳								